

Package: mbr (via r-universe)

September 12, 2024

Type Package

Title Mass Balance Reconstruction

Version 0.0.1.1

Author Hung Nguyen

Maintainer Hung Nguyen <ntthung@gmail.com>

Description Mass-balance-adjusted Regression algorithm for streamflow reconstruction at sub-annual resolution (e.g., seasonal or monthly). The algorithm implements a penalty term to minimize the differences between the total sub-annual flows and the annual flow. The method is described in Nguyen et al (2020) <[DOI:10.1002/essoar.10504791.1](https://doi.org/10.1002/essoar.10504791.1)>.

License GPL (>= 2.0)

Encoding UTF-8

LazyData true

Depends R (>= 3.5)

Imports data.table, dplyr, MASS, Matrix, Rfast, stats

RoxygenNote 7.1.1

Roxygen list(markdown = TRUE)

URL <https://github.com/ntthung/mbr>

BugReports <https://github.com/ntthung/mbr/issues>

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

Repository <https://critical-infrastructure-systems-lab.r-universe.dev>

RemoteUrl <https://github.com/critical-infrastructure-systems-lab/mbr>

RemoteRef HEAD

RemoteSha e5850b4229c6c0329de9229d78cb30ec2928a253

Contents

back_trans	2
calculate_metrics	3
colScale	3
colUnscale	4
cv_mb	5
KGE	6
lsq_mb	6
make_Z	7
mb_fit	8
mb_reconstruction	8
nRMSE	9
NSE	10
obj_fun	10
p1Seasonal	11
pc3seasons	12
prepend_ones	12
RE	13
rowScale	13
rowUnscale	14
Index	15

back_trans	<i>Back-transformation</i>
------------	----------------------------

Description

Transform the reconstructed values back to the flow space and convert to data.table

Usage

```
back_trans(hat, years, mus, sigmas, log.trans, N, season.names)
```

Arguments

hat	A vector of estimated flow in the transformed space.
years	A vector of all years in the study period
mus	A vector of means, one for each target.
sigmas	A vector of the standard deviations, one for each target.
log.trans	A vector containing the indices of the columns to be log-transformed.
N	The number of targets (number of seasons plus one for the annual reconstruction).
season.names	A character vector containing the names of the seasons

Value

A data.table with three columns: Q (the back-transformed streamflow), season, and year.

calculate_metrics	<i>Reconstruction metrics</i>
-------------------	-------------------------------

Description

Calculate reconstruction metrics from the instrumental period

Usage

```
calculate_metrics(sim, obs, z, norm.fun = mean)
```

Arguments

sim	A vector of reconstruction output for instrumental period
obs	A vector of all observations
z	A vector of left out indices in cross validation
norm.fun	The function (unquoted name) used to calculate the normalizing constant. Default is mean(), but other functions such as sd() can also be used. The function must take a vector as input and return a scalar as output, and must have an argument na.rm = TRUE.

Value

A named vector of performance metrics

Examples

```
calculate_metrics(rnorm(100), rnorm(100), z = 1:10)
calculate_metrics(rnorm(100), rnorm(100), z = 1:10, norm.fun = sd)
```

colScale	<i>Scale columns of a matrix</i>
----------	----------------------------------

Description

Same as base::scale() but much faster.

Usage

```
colScale(x, add_attr = TRUE)
```

Arguments

x	A matrix.
add_attr	If TRUE, the column means and standard deviations are returned as attributes. This is consistent with <code>base::scale()</code> .

Value

The scaled matrix.

Reference

This function was adopted from John Muschelli's code on [StackOverflow](#), but I changed the underlying functions to calculate mean and standard deviation from `matrixStats` to `Rfast`, which is much faster.

colUnscale	<i>Unscale columns of a matrix</i>
------------	------------------------------------

Description

Backtransform a matrix that was scaled before.

Usage

```
colUnscale(x, cm, csd)
```

Arguments

x	A matrix.
cm	A vector of column means
csd	A vector of column standard deviations

Value

The unscaled matrix

 cv_mb

Cross-validation

Description

Cross-validation

Usage

```
cv_mb(
  instQ,
  pc.list,
  cv.folds,
  start.year,
  lambda = 1,
  log.trans = NULL,
  force.standardize = FALSE,
  return.type = c("fval", "metrics", "metric means", "Q")
)
```

Arguments

instQ	Instrumental data, in the same order as pc.list. The "season" column must be a factor.
pc.list	List of PC matrices
cv.folds	A list containing the cross validation folds
start.year	The first year of record
lambda	The penalty weight
log.trans	A vector containing indices of the targets to be log-transformed. If no transformation is needed, provide NULL.
force.standardize	If TRUE, all observations are standardized. See Details.
return.type	The type of results to be returned. Several types are possible to suit multiple use cases. fval Only the objective function value (penalized least squares) is returned; this is useful for the outer optimization for site selection. metrics all performance metrics are returned. metric means the Tukey's biweight robust mean of each metric is returned. Q The predicted flow in each cross-validation run is returned. This is the most basic output, so that you can use it to calculate other metrics that are not provided by the package.

Value

A data.table containing cross-validation results (metrics, fval, or metric means) for each target.

Examples

```
cvFolds <- make_Z(1922:2003, nRuns = 50, frac = 0.25, contiguous = TRUE)
cv <- cv_mb(p1Seasonal, pc3seasons, cvFolds, 1750, log.trans = 1:3, return.type = 'metrics')
```

KGE

Kling-Gupta Efficiency

Description

Kling-Gupta Efficiency

Usage

```
KGE(yhat, y)
```

Arguments

yhat	Model outputs
y	Observations

Value

KGE value

Examples

```
KGE(rnorm(100), rnorm(100))
```

lsq_mb

Least square with mass balance penalty

Description

Least square with mass balance penalty

Usage

```
lsq_mb(hat, obs, lambda, mus, sigmas, log.seasons, log.ann, N, sInd)
```

Arguments

hat	A vector of estimated flow in the transformed space.
obs	A vector of observed flow in the transformed space.
lambda	Penalty weight.
mus	A vector of means, one for each target.
sigmas	A vector of the standard deviations, one for each target.
log.seasons	A vector containing the indices of the seasons that are log-transformed.
log.ann	TRUE if the annual reconstruction is log-transformed.
N	The number of targets (number of seasons plus one for the annual reconstruction).
sInd	Indices of the seasons, i.e, 1...N-1

Value

Objective function value: least squares plus a penalty term.

make_Z	<i>Make cross-validation folds.</i>
--------	-------------------------------------

Description

Make a list of cross-validation folds. Each element of the list is a vector of the cross-validation points for one cross-validation run.

Usage

```
make_Z(obs, nRuns = 30, frac = 0.1, contiguous = TRUE)
```

Arguments

obs	Vector of observations.
nRuns	Number of repetitions.
frac	Fraction of left-out points. For leave-one-out, use frac = 1, otherwise use any value less than 1. Default is 0.1 (leave-10%-out).
contiguous	Logical. If TRUE, the default, the left-out points are made in contiguous blocks; otherwise, they are scattered randomly.

Value

A list of cross-validation folds

Examples

```
Z <- make_Z(p1Seasonal$Qa, nRuns = 30, frac = 0.25, contiguous = TRUE)
```

mb_fit	<i>Fit parameters with mass balance criterion</i>
--------	---

Description

Fit parameters with mass balance criterion

Usage

```
mb_fit(X, Y, lambda, mus, sigmas, log.seasons, log.ann, N, sInd)
```

Arguments

X	Inputs, must have columns of 1 added
Y	Observed Dry, Wet, and Annual log-transformed flows
lambda	Penalty weight.
mus	A vector of means, one for each target.
sigmas	A vector of the standard deviations, one for each target.
log.seasons	A vector containing the indices of the seasons that are log-transformed.
log.ann	TRUE if the annual reconstruction is log-transformed.
N	The number of targets (number of seasons plus one for the annual reconstruction).
sInd	Indices of the seasons, i.e, 1...N-1

Value

A one-column matrix of beta value

mb_reconstruction	<i>Mass-balance-adjusted reconstruction</i>
-------------------	---

Description

Mass-balance-adjusted reconstruction

Usage

```
mb_reconstruction(
  instQ,
  pc.list,
  start.year,
  lambda = 1,
  log.trans = NULL,
  force.standardize = FALSE
)
```


Arguments

<code>instQ</code>	Instrumental data, in the same order as <code>pc.list</code> . The "season" column must be a factor.
<code>pc.list</code>	List of PC matrices. The first element is for the first season, second element for second season, and so on. The last element is for the annual reconstruction.
<code>start.year</code>	The first year of record
<code>lambda</code>	The penalty weight
<code>log.trans</code>	A vector containing indices of the targets to be log-transformed. If no transformation is needed, provide NULL.
<code>force.standardize</code>	If TRUE, all observations are standardized. See Details.

Value

A `data.table` with the following columns: `season`, `year`, `Q`, and `lambda`.

Details

If some targets are log transformed and some are not, they will have different scales, which affects the objective function. In this case the observations will be standardized so that they are in the same range. Otherwise, standardization are skipped for speed. However, in some cases you may want to standardize any ways, for example when flows in some months are much larger than in other months. In this case, set `force.standardize = TRUE`.

Examples

```
mb_reconstruction(p1Seasonal, pc3seasons, 1750, lambda = 1, log.trans = 1:3)
```

nRMSE	<i>Normalized root-mean-square error</i>
-------	--

Description

RMSE is normalized by the normalization constant

Usage

```
nRMSE(yhat, y, normConst)
```

Arguments

<code>yhat</code>	Model outputs
<code>y</code>	Observations
<code>normConst</code>	The normalization constant

Value

normalized RMSE value

Examples

```
x <- rnorm(100)
y <- rnorm(100)
nRMSE(x, y, sd(y))
```

NSE	<i>Nash-Sutcliffe Efficiency</i>
-----	----------------------------------

Description

Nash-Sutcliffe Efficiency

Usage

```
NSE(yhat, y)
```

Arguments

yhat	Model outputs
y	Observations

Value

NSE value

Examples

```
NSE(rnorm(100), rnorm(100))
```

obj_fun	<i>Objective function from parameters</i>
---------	---

Description

This is a wrapper for `lsq_mb()`. It first calculates `hat`, then calls `lsq_mb()`. This is used in `optim()`, so it returns a scalar.

Usage

```
obj_fun(beta, X, Y, lambda, mus, sigmas, log.seasons, log.ann, N, sInd)
```

Arguments

beta	Parameters
X	Inputs, must have columns of 1 added
Y	Observed Dry, Wet, and Annual log-transformed flows
lambda	Penalty weight.
mus	A vector of means, one for each target.
sigmas	A vector of the standard deviations, one for each target.
log.seasons	A vector containing the indices of the seasons that are log-transformed.
log.ann	TRUE if the annual reconstruction is log-transformed.
N	The number of targets (number of seasons plus one for the annual reconstruction).
sInd	Indices of the seasons, i.e, 1...N-1

Value

Objective function value

p1Seasonal	<i>Seasonal streamflow at P.1 station</i>
------------	---

Description

Streamflow at P.1 station (Chiang Mai, Thailand) for three reconstruction targets: dry season (NJ, Nov-Jun), wet season (JO, Jul-Oct), and water year (WY, Nov-Oct), as used by Nguyen et al (2020).

Usage

p1Seasonal

Format

A data table with 246 rows and 3 variables:

season a factor with three levels: "NJ", "JO", and "WY"

year integer, from 1922 to 2003

Qa Annual flow for each target

Source

<https://www.essoar.org/doi/10.1002/essoar.10504791.1>

References

Nguyen, H. T. T., Galelli, S., Xu, C., & Buckley, B. (2020). Multi-Proxy, Multi-Season Streamflow Reconstruction with Mass Balance Adjustment. Earth and Space Science Open Archive, 22. <https://doi.org/10.1002/essoar.10504791.1>

pc3seasons

Principal components of tree rings

Description

Principal components of the Southeast Asian Dendrochronology Network, after appropriate sites have been selected for each season.

Usage

pc3seasons

Format

A list with three elements (NJ, JO, and WY), each element is a principal component matrix.

Source

<https://www.essoar.org/doi/10.1002/essoar.10504791.1>

References

Nguyen, H. T. T., Galelli, S., Xu, C., & Buckley, B. (2020). Multi-Proxy, Multi-Season Stream-flow Reconstruction with Mass Balance Adjustment. *Earth and Space Science Open Archive*, 22. <https://doi.org/10.1002/essoar.10504791.1>

prepend_ones

Prepend a column of ones

Description

Prepend a column of ones

Usage

prepend_ones(x)

Arguments

x The input matrix

Value

x with a column of ones prepended, which is named 'Int' for 'intercept'

RE	<i>Reduction of Error</i>
----	---------------------------

Description

Reduction of Error

Usage

```
RE(yhat, y, yc_bar)
```

Arguments

yhat	Model outputs in the validation set
y	Observations in the validation set
yc_bar	Mean observations in the calibration set

Value

RE value

Examples

```
x <- rnorm(100)
y <- rnorm(100)
yc_bar <- mean(x[1:50])
RE(x[51:100], y[51:100], yc_bar)
```

rowScale	<i>Scale rows of a Matrix</i>
----------	-------------------------------

Description

Similar to [colScale](#)

Usage

```
rowScale(x, add_attr = TRUE)
```

Arguments

x	A matrix.
add_attr	If TRUE, the column means and standard deviations are returned as attributes. This is consistent with base::scale() .

Value

The scaled matrix.

rowUnscale	<i>Unscale rows of a matrix</i>
------------	---------------------------------

Description

Backtransform a matrix that was scaled before.

Usage

```
rowUnscale(x, rm, rsd)
```

Arguments

x	A matrix.
rm	A vector of row means
rsd	A vector of row standard deviations

Value

The unscaled matrix

Index

* datasets

p1Seasonal, 11
pc3seasons, 12

back_trans, 2
base::scale(), 4, 13

calculate_metrics, 3
colScale, 3, 13
colUnscale, 4
cv_mb, 5

KGE, 6

lsq_mb, 6

make_Z, 7
mb_fit, 8
mb_reconstruction, 8

nRMSE, 9
NSE, 10

obj_fun, 10

p1Seasonal, 11
pc3seasons, 12
prepend_ones, 12

RE, 13
rowScale, 13
rowUnscale, 14